

# Specification tables and installation diagrams



	B9820-5-M	B9978-5-M	B9879-5-M	B8871-5-M	B5741-5-M B5741-5-B
<b>Features</b>					
True fan - Ventitherm®	•	•	•	•	•
Fan controlled defrosting	•	•	•	•	•
Vigorous steam	•				
Interval steam plus	•				
Interval steam	•				
Rotitherm roasting	•	•	•	•	•
Conventional cooking	•	•	•	•	•
Fan baking	•	•	•	•	•
80° Keep warm	•	•	•	•	•
Base heat finishing	•	•	•	•	•
Top heat browning					
Low temperature cooking and slow cook	•	•	•	•	
Full width/dual circuit grill	•	•	•	•	•
Economy grill	•	•	•	•	•
Fast heat up	•	•	•	•	•
Food probe	•	•	•	•	
<b>Control</b>					
Digital controls	•	•	•	•	
Retractable controls					•
Rotary controls					
Digital display	•	•	•	•	•
Digital temperature control	•	•	•	•	•
Fully programmable electronic clock	•	•	•	•	•
Electronic minute minder	•	•	•	•	•
Digital controls with menu guided cooking	•	•	•	•	
<b>Performance</b>					
Oven temperature range °C	30-250	30-250	30-300	30-300	30-300
Energy efficiency class 1)	A	A	A	A	A
Energy efficiency class in mode Static/Fan	Fan	Fan	Fan	Fan	Fan
Cooktime standard load static minutes	53	48	48	48	48
Cooktime standard load fan minutes	43	43	42	42	42
Energy consumption static kWh	1.19	0.91	0.91	0.91	0.91
Energy consumption fan kWh	0.79	0.79	0.79	0.79	0.79
Standby power W	1.2	0.5	0.5	0.5	1.7
Oven door(s) glazing (Q=quadruple T=triple, D=double)	T	Q	Q	Q	Q
Pyroluxe oven cleaning 2)		•	•	•	•
Catalytic lining/liners					
Diamond glazed enamel interior	•	•			
Cooling fan	•	•	•	•	•
<b>Design</b>					
Anti-fingerprint stainless steel	•	•	•	•	•
<b>Accessories</b>					
Telescopic runners	Optional	Optional	•	Optional	Optional
Chrome grid runners	•	•	•	•	•
Chrome auto-stop non-tip shelves	2	2	3	2	2
Grill/meat pan	•/•	•/•	•/•	•/•	•/•
Pizza stone			•		
<b>Product dimensions</b>					
<b>Internal oven dimensions</b>					
Volume (usage) litres	50	50	50	50	51
Height mm	310	310	310	310	310
Width mm	400	400	400	405	405
Depth mm	407	407	407	407	410
<b>Appliance dimensions 3)</b>					
Height 4) mm	594	594	594	594	594
Width mm	592	594	594	594	594
Depth mm	567	567	567	567	567
Net weight kg	49	45	49	40	41
<b>Aperture dimensions</b>					
Height mm	590	590	590	590	590
Width mm	560	560	560	560	560
Depth mm	550	550	550	550	550
<b>Packaging dimensions</b>					
Height mm	690	700	700	700	700
Width mm	660	660	660	660	660
Depth mm	700	710	710	710	710
Gross weight kg	53	49	53	44	45
<b>Other</b>					
Connected load kW	3.5	3.5	3.5	3.5	3.5
Fuse rating A	16	16	16	16	16
Oven/grill power (max) kW	3.5/2.9	3.5/2.9	3.5/2.9	3.5/2.9	3.5/2.9
Steam power output kW	1.8				
Interior lights W	2 x 25	2 x 25	1 x 20 (H) 1 x 40	1 x 20 (H) 1 x 40	1 x 40
Interior lights position	Side & back	Side & back	Side & back	Side & back	Back
Compact hinge	•	•	•	•	•
<b>Safety and interference suppression</b>					
Low voltage directive LVD	•	•	•	•	•
Electromagnetic compatibility EMC	•	•	•	•	•
<b>Literature supplied</b>					
Operation and installation instructions	•	•	•	•	•

1) Energy efficiency class based on a scale of A (most efficient) to G (least efficient).

2) Pyroluxe® cleaning : 5.0kWh.

3) Refer to user instructions before cutting out.

4) 593mm if built under worktop or hob for all models.

		B99697-5-M B99698-5-M	B4115-5-M	B4101-5-M B4101-5-B	B3101-5-M B3101-5-B B3101-5-W	B2100-5-W B2100-5-M	B8139-5-M
<b>Features</b>							
True fan - Ventitherm®		•	•	•	•	•	•
Fan controlled defrosting		•	•	•	•	•	
Vigorous steam							
Interval steam plus							
Interval steam							
Rotitherm roasting		•	•	•	•	•	•
Conventional cooking		•	•	•			•
Fan baking		•	•	•			•
80° Keep warm		•					
Base heat finishing		•	•	•			•
Top heat browning							•
Low temperature cooking and slow cook		•					
Full width/dual circuit grill		•	•	•	•	•	•
Economy grill			•	•	•		•
Fast heat up		•					
Food probe							•
<b>Control</b>							
Digital controls		•					
Retractable controls			•	•	•		•
Rotary controls						•	
Digital display		•					•
Digital temperature control		•					
Fully programmable electronic clock		•	•	•	•	•	•
Electronic minute minder		•	•	•	•	•	•
Digital controls with menu guided cooking		•					
<b>Performance</b>							
Oven temperature range	°C	30-250	50-275	50-275	50-275	50-275	30-290
Energy efficiency class 1)		A	A	A	A	A	B
Energy efficiency class in mode Static/Fan		Fan	Fan	Fan	Fan	Fan	Fan
Cooktime standard load static	minutes	43	47	45	NA	NA	53
Cooktime standard load fan	minutes	41	42	43	42	42	50
Energy consumption static	kWh	0.79	0.9	0.87	NA	NA	1.5
Energy consumption fan	kWh	0.79	0.79	0.79	0.79	0.79	1.19
Standby power	W	2	1	1.3	1.3	1.3	2
Oven door(s) glazing (Q=quadruple T=triple, D=double)		Q	T	T	T	D	T
Pyroluxe oven cleaning 2)		•					
Catalytic lining/liners			•	•	•		
Diamond glazed enamel interior						•	•
Cooling fan		•	•	•	•	•	•
<b>Design</b>							
Anti-fingerprint stainless steel		•	•	•	•	•	•
<b>Accessories</b>							
Telescopic runners		3	Optional	Optional	Optional	Optional	
Chrome grid runners		•	•	•	•	•	•
Chrome auto-stop non-tip shelves		3	2	2	2	2	1
Grill/meat pan		•/•	•	•	•	•	•/•
Pizza stone							•
<b>Product dimensions</b>							
<b>Internal oven dimensions</b>							
Volume (usage)	litres	53	53	51	50	51	69
Height	mm	335	310	310	310	310	310
Width	mm	395	440	405	400	405	586
Depth	mm	400	388	410	407	410	380
<b>Appliance dimensions 3)</b>							
Height 4)	mm	590	594	594	594	594	480
Width	mm	594	594	594	594	594	892
Depth	mm	560	567	567	567	567	556
Net weight	kg	39.5	45	35	34	30.5	68
<b>Aperture dimensions</b>							
Height	mm	580	590	590	590	590	475
Width	mm	560	560	560	560	560	860
Depth	mm	550	550	550	550	550	550
<b>Packaging dimensions</b>							
Height	mm	660	700	700	700	700	560
Width	mm	630	660	660	660	660	1000
Depth	mm	670	710	710	710	710	675
Gross weight	kg	41	49	39	38	34.5	77
<b>Other</b>							
Connected load	kW	3.1	3.5	3.5	3	3	3.6
Fuse rating	A	13	16	16	13	13	16
Oven/grill power (max)	kW	3.1/2.5	3.5/2.9	3.5/2.9	3.0/2.9	3.0/2.9	3.6/3.4
Steam power output	kW						
Interior lights	W	1 x 25	1 x 40	1 x 40	1 x 40	1 x 25	2 x 25(H)
Interior lights position		Back	Back	Back	Back	Back	Sides
Compact hinge		•	•	•	•	•	•
<b>Safety and interference suppression</b>							
Low voltage directive	LVD	•	•	•	•	•	•
Electromagnetic compatibility	EMC	•	•	•	•	•	•
<b>Literature supplied</b>							
Operation and installation instructions		•	•	•	•	•	•

1) Energy efficiency class based on a scale of A (most efficient) to G (least efficient).

2) Pyroluxe® cleaning : 5.0kWh.

3) Refer to user instructions before cutting out.

4) 593mm if built under worktop or hob for all models.

		D8810-6-M	D4111-6-M	D3101-6-M D3101-6-W D3101-6-B	U8810-6-M	U4111-6-M U4111-6-W
		Top/Main	Top/Main	Top/Main	Top/Main	Top/Main
<b>Features</b>						
True fan - Ventitherm®		•/•	/•	/•	•/•	/•
Fan controlled defrosting		•/•	/•	/•	•/•	/•
Rotitherm roasting		•/•	/•	/•	•/•	
Conventional cooking		/•	•/•	•/	/•	•/
Fan baking		•/•	/•		•/•	
80° Keep warm		/•			/•	
Top heat finishing			•/	•/		•/
Base heat finishing		•/•	•/•	•/	•/•	•/
Low temperature cooking and slow cook		•/•			•/•	
Full width/dual circuit grill		•/•	•/•	•/	•/•	•/
Economy grill		•/•	•/•	•/	•/•	•/
<b>Control</b>						
Digital controls		•			•	
Retractable controls			•	•		•
Digital display with interactive cooking		•			•	
Digital temperature control		•			•	
Fully programmable electronic clock		Main	Main	Main	Main	Main
Electronic minute minder		•	•	•	•	•
<b>Performance</b>						
Energy efficiency class 1)		A/A	A/A	A/A	A/A	A/A
Energy efficiency class in mode Static/Fan		Fan/Fan	Static/Fan	Static/Fan	Fan/Fan	Static/Fan
Cooktime standard load static	minutes	NA	52/49	52/NA	51/50	52/NA
Cooktime standard load fan	minutes	49/44	NA/44	NA/44	49/48	NA/48
Energy consumption static	kWh	0.79/0.79	0.79/0.88	0.79/NA	0.89/0.79	0.79/NA
Energy consumption fan	kWh	0.79/0.79	NA/0.79	NA/0.79	0.79/0.79	NA/0.79
Standby power	W	0.6/0.6	1.3/1.3	1.3/1.3	0.6/0.6	1.3/1.3
Oven door(s) glazing (T=triple, D=double)		T	D	D	T	D
Catalytic lining/liners		•	•	•	•	•
Diamond glazed enamel interior				•		
Cooling fan		•	•	•	•	•
<b>Design</b>						
Anti-fingerprint stainless steel		•	•	•	•	•
<b>Accessories</b>						
Chrome grid runners		•	•	•	•	•
Chrome auto-stop non-tip shelves		1/2	1/2	1/2	1/2	1/2
Grill/meat pan		•	•	•	•	•
<b>Product dimensions</b>						
<b>Internal oven dimensions</b>						
Volume (usage)	litres	37/56	37/56	37/56	37/40	37/40
Height	mm	208/338	208/338	208/338	208/243	208/243
Width	mm	400/400	400/400	400/400	400/400	400/400
Depth	mm	441/415	441/415	441/415	441/415	441/415
<b>Appliance dimensions 2)</b>						
Height	mm	888	888	888	715	715
Width	mm	594	594	594	594	594
Depth	mm	548	548	548	548	548
Net weight	kg	53	53	53	48	48
<b>Aperture dimensions</b>						
Height	mm	875	875	875	720	720
Width	mm	560	560	560	600	600
Depth	mm	550	550	550	560	560
<b>Packaging dimensions</b>						
Height	mm	965	965	965	805	805
Width	mm	660	660	660	660	660
Depth	mm	705	705	705	705	705
Gross weight	kg	55	55	55	53	53
<b>Other</b>						
Connected load	kW	5.8	5.3	4.3	5.7	4.3
Fuse rating	A	30	30	30	30	30
Oven power (max)	kW	2.35/2.98	2.35/2.98	2.35/1.97	2.99/1.9	2.35/1.98
Grill power (max)	kW	2.3/1.9	2.3/1.9	2.3/NA	2.3/1.9	2.3/NA
Interior lights	W	1 x 25	1 x 25	1 x 25	1 x 25	1 x 25
Interior lights position		Side	Back	Back	Back	Back
Compact hinge		•	•	•	•	•
<b>Safety and interference suppression</b>						
Low voltage directive	LVD	•	•	•	•	•
Electromagnetic compatibility	EMC	•	•	•	•	•
<b>Literature supplied</b>						
Operation and installation instructions		•	•	•	•	•

1) Energy efficiency class based on a scale of A (most efficient) to G (least efficient).

2) Refer to user instructions before cutting out.

	MCC3880EM	MCD3880EM	MCD2662EM	MCD1762EM	MC1752EM	MC1762EM	MC2662EW MC2662B MC2662M
<b>Features</b>							
Combi microwave, fan oven and grill	•						
Duo microwave and grill		•	•	•			
Solo microwave					•	•	•
QUARTZ grill			•	•	•	•	•
Grill	•	•					
Convection (Fan oven)							
Auto defrost by weight programmes	4	4	7	7	7	7	7
Auto cook by weight programmes	4	4	9	9	6	6	7
<b>Control</b>							
Electronic push controls	8	8	7	4	4	4	7
Control knobs			1	1	1	1	1
Electronic clock/programmer	•	•	•	•	•	•	•
Quickstart	•	•	•	•	•	•	•
<b>Performance</b>							
Microwave output (IEC 705)	1000W	1000W	900W	800W	800W	800W	900W
Heating category 1)	E	E	E	E	E	E	E
Grill output	1500W	1500W	1000W	1000W			
Convection oven output	1600W						
Microwave power levels	5	5	5	5	5	5	5
Total load rating kW	3.4	3.3	2.4	2.2	1.2	1.2	1.3
Fuse rating A	15	15	13	13	13	13	13
Power save mode			•	•	•	•	•
Programme end signal	•	•	•	•	•	•	•
Child lock			•	•	•	•	•
<b>Design</b>							
Anti-fingerprint stainless steel	•	•	•	•	•	•	•
Fully built-in	•	•	•	•	•	•	•
Under counter installation	•	•			•	•	•
In-column installation	•	•	•	•	•	•	•
<b>Product dimensions</b>							
Oven volume litres	38	38	26	17	17	17	26
Height mm	455	455	459	371	371	371	459
Width mm	594	594	594	594	494	594	594
Depth mm	542	542	437	316	316	316	437
Net weight kg	35	35	18.5	16	15.5	15.5	18
<b>Built-in dimensions 2)</b>							
Built-in height mm	450	450	450	360	360	360	450
Built-in width mm	560	560	560	560	460	560	560
Built-in depth mm	550	550	500	300	300	300	500
<b>Packaging dimensions</b>							
Height mm	535	535	525	475	475	475	525
Width mm	680	680	660	684	684	684	660
Depth mm	660	660	535	418	418	418	535
Gross weight kg	38	38	21.5	19	18	18	21

1) Heating category of the microwave oven in line with government guidelines.

2) Installation aperture dimensions, for full details refer to installation guidelines.

	KB9820E-M	KB9810E-M	KB9800E-M	KM9800E-M
<b>Features</b>				
Microwave		•		•
Microwave defrosting		•		•
Microwave auto defrost by weight		•		•
Microwave auto cook by weight		•		•
Microwave and grill		•		•
Microwave and True fan - Ventitherm®		•		
True fan - Ventitherm®	•	•	•	
Fan controlled defrosting	•	•	•	
Vigorous steam	•			
Interval steam	•			
Rotitherm roasting	•	•	•	
Low temperature cooking & slow cook	•		•	
Variable grill	•	•	•	•
<b>Control</b>				
Digital touch controls	•	•	•	•
Digital display	•	•	•	•
Digital temperature control	•	•	•	•
Fully programmable electronic clock	•	•	•	•
Electronic minute minder	•	•	•	•
<b>Performance</b>				
Fan/convection oven output	1650W	1650W	1650W	-
Grill output	1500W	1500W	1500W	1500W
Microwave output		1000W		1000W
Steam power output	1800W			
Heating category 1)		E		E
Energy efficiency class 2)	A	N/A	B	N/A
Energy efficiency class in mode static/fan	Fan	N/A	Fan	N/A
Oven temperature range °C	30-320	30-250	30-250	N/A
Cooktime standard load fan minutes	41	N/A	60	N/A
Energy consumption fan kWh	0.59	N/A	0.79	N/A
Standby power W	1.4	1.4	1.4	1.4
Oven door(s) glazing (Q=quadruple T=triple, D=double)	Q	Q	Q	Q
Catalytic liners	Roof		Roof	
Diamond glazed enamel interior	•	•	•	•
Cooling fan	•	•	•	•
<b>Design</b>				
Anti-fingerprint stainless steel	•	•	•	•
<b>Accessories</b>				
Chrome grid runners	•	•	•	•
Chrome auto-stop non-tip shelves	1	1	1	1
Grill/meat pan	•	•	•	•
<b>Product dimensions</b>				
<b>Internal oven dimensions</b>				
Volume (usage) litres	31	31	31	31
Height mm	205	205	205	205
Width mm	400	400	400	400
Depth mm	378	378	378	378
<b>Appliance dimensions</b>				
Height mm	388	388	388	388
Width mm	592	592	592	592
Depth mm	567	567	567	567
Net weight kg	28	43	27.5	41
<b>Aperture dimensions</b>				
Height 3) mm	380	380	380	380
Width mm	560	560	560	560
Depth mm	550	550	550	550
<b>Packaging dimensions</b>				
Height mm	480	480	480	480
Width mm	670	670	670	670
Depth mm	720	720	720	720
Gross weight kg	31.5	46.5	31	44.5
<b>Other</b>				
Connected load kW	3.7	3.7	3.7	3.7
Fuse rating A	16	16	16	16
Oven/grill power (max) kW	1.65/1.5	1.65/1.5	1.65/1.5	0/1.5
Interior lights W	25 (H)	26 (H)	25	25
Interior lights position	Side	Side	Side	Side
Compact hinge	•	•	•	•
<b>Safety and interference suppression</b>				
Low voltage directive LVD	•	•	•	•
Electromagnetic compatibility EMC	•	•	•	•
<b>Literature supplied</b>				
Operation and installation instructions	•	•	•	•

1) Heating category of the microwave in line with government guidelines.

2) Energy efficiency class based on a scale of A (most efficient) to G (least efficient).

3) Refer to installation diagram for full details.

		KD81403E*	KD82103E*	KD82903E*
<b>Features</b>				
Cups and glasses warming	40°C	•	•	•
Crockery warming	60°C	•	•	•
Food warming	80°C (Maximum)	•	•	•
Defrosting	30°C (Minimum)	•	•	•
Heating element		•	•	•
<b>Control</b>				
Fan air circulation		•	•	•
Rotary control knob		•	•	•
Variable temperature control		•	•	•
On/off LED		•	•	•
Anti-slip mat		•	•	•
Number of place settings		6	9	12
Temperature range	°C	30-85	30-85	30-85
<b>Technical</b>				
Total load rating	kW	0.43	0.55	0.55
Fuse rating	A	13	13	13
Oven/grill power (max)	kW	0.40	0.50	0.50
<b>Product dimensions</b>				
Height	mm	140	215	295
Width	mm	594	595	594
Depth	mm	535	523	535
Net weight	kg	18	24	27
<b>Built-in dimensions</b>				
Built-in height	mm	145	215	295
Built-in width	mm	560	560	560
Built-in depth	mm	550	550	550
<b>Packaging dimensions</b>				
Height	mm	250	300	380
Width	mm	645	645	648
Depth	mm	670	670	670
Gross weight	kg	20.3	26.4	29.6
<b>Safety and interference suppression</b>				
Low voltage directive	LVD	•	•	•
Electromagnetic compatibility	EMC	•	•	•
<b>Literature supplied</b>				
Operation and installation instructions		•	•	•

\*Food must be a minimum of 80°C prior to placing in the warming drawer.

		PE3810-M	PE8039-M	PKD6070-M
		Accessory drawer		
Performance				
Working pressure	Bar	16	12	
Control				
Electronic touch controls		•	•	
LED display		•	•	
Pre-programmed coffee selection		•	•	
Water sensor with LED when refill required		•	•	
Steam/water spout with LED indicators		•	•	
Design				
Height adjustable coffee dispenser		•		
Lamp		Halogen	20W Halogen	
Product dimensions 1)				
Height	mm	378	378	70
Width	mm	594	594	592
Depth	mm	415	380	502
Net weight	kg	22.2	22.5	9.6
Built-in dimensions				
Built-in height	mm	380	380	70
Built-in width	mm	560	560	560
Built-in depth	mm	550	550	550
Packaging dimensions				
Height	mm	505	465	160
Width	mm	650	670	630
Depth	mm	510	605	585
Gross weight	kg	275	25	10.2
Electrical connection				
Connected load	kW	1.35	1.15	
Fuse rating	A	13	13	

1) Refer to installation diagram for full details.



	FM4800TYAN	FM4863K-AN	FM4803K-AN	FM4513K-AN
	Teppan Yaki	1 zone induction wok	2 zone induction	2 zone ceramic
<b>Features</b>				
Fuel type	Electric	Electric	Electric	Electric
LPG conversion kit				
Rotary knobs/touch controls	Touch	Touch	Touch	Touch
<b>Specification</b>				
Number of cooking zones	2	1	2	2
<b>Zone specification</b>				
Front spec	Induction	Induction	Induction	Hilight
Front rating 1) kW	1.4	2.3/3.2	2.3/3.7	0.7/1.7
Front diameter mm	145	300	210	120/180
Rear spec	Induction		Induction	Hilight
Rear rating 1) kW	1.4		1.45/1.8	1.2
Rear diameter mm	145		145	145
Grill rating 1) kW				
Pot sensors	•	•	•	
Gas safety shut off				
<b>Electrical connection</b>				
Voltage V	220/240	220-240	230	230
Frequency Hz	50/60	50/60	50	50
Total rating kW	2.8	3.2	3.7	2.9
Cable length mm	1400	1400	1500	2000
<b>Product dimensions 2)</b>				
Height (above worktop) mm	6	10	12	11
Overall height mm	64	135	49	49
Width mm	360	360	360	360
Depth mm	520	520	520	520
Net weight kg	10.2	11.2	7	6
<b>Aperture dimensions 2)</b>				
Height mm	58	145	58	50
Width mm	340	340	340	340
Depth mm	490	490	490	490
<b>Packaging dimensions</b>				
Height mm	175	400	165	165
Width mm	705	470	428	428
Depth mm	640	600	575	575
Gross weight kg	13.8	14.6	8	7
<b>Safety and interference suppression</b>				
Low voltage directive LVD	•	•	•	•
Electromagnetic compatibility EMC	•	•	•	•
Gas directive				
<b>Literature supplied</b>				
Operation and installation instructions	•	•	•	•

1) For gas conversion purpose 3.450 BTU = 1kW.

2) Refer to installation diagrams if installing more than one Front-line unit or if installing a gas unit.

3) Can be installed above cupboards or ovens (installation kit NOT required). Installation above a drawer is not recommended.

4) Electrical supply for ignition only.

		FM4500GR-A	FM4360G-AN	FM4300G-AN
		Barbecue grill	Wok burner	2 zone gas
<b>Features</b>				
Fuel type		Electric	Natural Gas <sup>3)</sup>	Natural Gas <sup>3)</sup>
LPG conversion kit				Included
Rotary knobs/touch controls		Touch	Rotary	Rotary
<b>Specification</b>				
Number of cooking zones		1	1	2
<b>Zone specification</b>				
Front spec			Double Crown	Semi-rapid burner
Front rating 1)	kW		3.7	1.9
Front diameter	mm		130	74
Rear spec				Rapid burner
Rear rating 1)	kW			3
Rear diameter	mm			104
Grill rating 1)	kW	2		
Pot sensors				
Gas safety shut off			•	•
<b>Electrical connection</b>				
Voltage	V	220/240	220/240	220-240
Frequency	Hz	50	50 <sup>4)</sup>	50 <sup>4)</sup>
Total rating	kW	2	0.6	0.6
Cable length	mm	2000	1800	1800
<b>Product dimensions 2)</b>				
Height (above worktop)	mm	25	11	11
Overall height mm		111	66	66
Width	mm	360	360	360
Depth	mm	520	520	520
Net weight	kg	9	7.2	7.8
<b>Aperture dimensions 2)</b>				
Height	mm	100	56	56
Width	mm	340	340	340
Depth	mm	490	490	490
<b>Packaging dimensions</b>				
Height	mm	370	192	165
Width	mm	615	428	428
Depth	mm	435	575	575
Gross weight	kg	13	8	8.5
<b>Safety and interference suppression</b>				
Low voltage directive	LVD	•	•	•
Electromagnetic compatibility	EMC	•	•	•
Gas directive			•	•
<b>Literature supplied</b>				
Operation and installation instructions		•	•	•

1) For gas conversion purpose 3.450 BTU = 1kW.

2) Refer to installation diagrams if installing more than one Front-line unit or if installing a gas unit.

3) Can be installed above cupboards or ovens (installation kit NOT required). Installation above a drawer is not recommended.

4) Electrical supply for ignition only.

	98030KF-SN HK854400FB	HK854400FB	78031KF-N HK764400FB	HK854220FB	HK854200FB	HK654200FB
	Induction hob	Induction hob	Induction hob	Induction hob	Induction hob	Induction hob
<b>Features</b>						
Number of cooking zones	3	4	4	4	4	4
Control position	Front	Front	Split sides	Front	Front	Front
Control type	Direktouch touch controls	Direktouch touch controls	Direktouch touch controls	Direktouch touch controls	Direktouch touch controls	Direktouch touch controls
Residual heat/hob on indicators	•	•	•	•	•	•
Electronic timer	•	•	•	•	•	•
Child lock	•	•	•	•	•	•
Function lock	•	•	•	•	•	•
Auto cut-off	•	•	•	•	•	•
Number of booster zones	3	4	4	4	4	4
Stop+Go	•	•	•	•	•	•
Automatic heat up (AUTOMAX)	•	•	•	•	•	•
Pot sensors	•	•	•	•	•	•
<b>Zone specification</b>						
Front left spec 1)	I	I	I	I	I	I
Front left rating kW	2.3/3.2	2.3/3.2	2.3/3.2	1.8/2.8	2.3/3.7	2.3/3.7
Front left diameter mm	210	210	210	180	210	210
Rear left spec 1)		I	I	I	I	I
Rear left rating kW		2.3/3.2	2.3/3.2	1.8/2.8	1.85/2.5	1.85/2.5
Rear left diameter mm		210	210	180	180	180
Front middle spec 1)	I			I		
Front middle rating kW	2.3/3.2			1.4/1.8		
Front middle diameter mm	210			145		
Rear middle spec 1)						
Rear middle rating kW						
Rear middle diameter mm						
Front right spec 1)	I	I	I		I	I
Front right rating kW	2.3/3.2	2.3/3.2	2.3/3.2		1.85/2.5	1.4/1.8
Front right diameter mm	210	210	210		180	145
Rear right spec 1)		I	I	I	I	I
Rear right rating kW		2.3/3.2	2.3/3.2	2.4/3.7	1.4/1.8	1.85/2.5
Rear right diameter mm		210	210	280	145	180
<b>Electrical connection</b>						
Total rating (max.) kW	6.9	7.4	7.4	7.4	7.4	7.4
Fuse rating A	30	30	30	30	30	30
<b>Product dimensions 2)</b>						
Height (above worktop) 3)	5	5	5	5	5	5
Width mm	910	780	710	780	780	590
Depth mm	410	520	520	520	520	520
Net weight kg	12.1	12.2	11.8	12.1	11.6	10.1
<b>Aperture dimensions 4)</b>						
Height mm	43	50	43	51	51	51
Width mm	880	750	680	750	750	560
Depth mm	380	490	490	490	490	490
<b>Packaging dimensions</b>						
Height mm	115	125	115	115	115	115
Width mm	995	995	680	865	865	690
Depth mm	575	645	575	575	575	575
Gross weight kg	15.4	13.1	13.1	13.3	12.5	11.6
<b>Safety and interference suppression</b>						
Low voltage directive LVD	•	•	•	•	•	•
Electromagnetic compatibility EMC	•	•	•	•	•	•
<b>Literature supplied</b>						
Operation and installation instructions	•	•	•	•	•	•

1) HI = Hiilght zone; I = Induction.

2) For full installation aperture dimensions see installation instructions.

3) Hob height: is above worktop only.

4) Refer to user instructions before cutting out.

	68002KF-N HK634200FB	67160KF-N HK634110FB	96931KF-N HK955070FB	96931KFE-N HK955070CB	76331KF-N HK854071FB	79331KF-N HK754070FB
	Induction hob	Induction hob	Ceramic hob	Ceramic hob	Ceramic hob	Ceramic hobs
<b>Hob features</b>						
Number of cooking zones	4	4	5	5	4	4
Control position	Front	Front	Front	Front	Front	Split sides
Control type	Touch controls	Touch controls	Direktouch touch controls	Direktouch touch controls	Direktouch touch controls	Direktouch touch controls
Residual heat/hob on indicators	•	•	•	•	•	•
Electronic timer	•	•	•	•	•	•
Child lock	•	•	•	•	•	•
Function lock	•	•	•	•	•	•
Auto cut-off	•	•	•	•	•	•
Number of booster zones	2	2				
Stop+Go		•	•	•	•	•
Automatic heat up (AUTOMAX)		•	•	•	•	•
Pot sensors	•	•				
<b>Zone specification</b>						
Front left spec 1)	I	I	HI	HI	Triple HI	Triple HI
Front left rating kW	2.2/3.1	2.2/3.1	1.8	1.2	0.8/1.6/2.3	0.8/1.6/2.3
Front left diameter mm	210	210	180	145	120/175/210	120/175/210
Rear left spec 1)	I	I	HI	HI	HI	HI
Rear left rating kW	1.4	1.4/2.5	1.2	1.8	1.2	1.2
Rear left diameter mm	140	145	145	180	145	145
Front middle spec 1)			Triple HI	Triple HI		
Front middle rating kW			1.05/1.95/2.7	1.05/1.95/2.7		
Front middle diameter mm			145/210/270	145/210/270		
Rear middle spec 1)						
Rear middle rating kW						
Rear middle diameter mm						
Front right spec 1)	I	HI	HI	HI	HI	HI
Front right rating kW	1.8/2.8	1.2	1.8	1.8	1.2	1.8
Front right diameter mm	180	145	180	180	145	180
Rear right spec 1)	I	Dual HI	Multi HI	Multi HI	Multi HI	Multi HI
Rear right rating kW	1.8	0.7/ 1.7	1.4/2.2	1.4/2.2	1.5/2.6	1.4/2.2
Rear right diameter mm	180	120/180	170 x 265	170 x 265	165 x 290	170 x 265
<b>Electrical connection</b>						
Total rating (max.) kW	7.4	6.5	7.9	7.9	7.3	7.5
Fuse rating A	30	30	30	30	30	30
<b>Product dimensions 2)</b>						
Height (above worktop) 3)	5	5	5	5	5	5
Width mm	590	590	910	1029	780	710
Depth mm	520	520	520	519	520	520
Net weight kg	11.0	10.6	12.5	11.6	9.7	9.3
<b>Aperture dimensions 4)</b>						
Height mm	51	51	43	43	43	43
Width mm	560	560	880	995	750	680
Depth mm	490	490	490	490	490	490
<b>Packaging dimensions</b>						
Height mm	115	115	115	115	115	130
Width mm	745	745	995	1105	865	795
Depth mm	575	575	575	575	575	595
Gross weight kg	12.2	11.5	13.9	15.3	10.9	10.6
<b>Safety and interference suppression</b>						
Low voltage directive LVD	•	•	•	•	•	•
Electromagnetic compatibility EMC	•	•	•	•	•	•
<b>Literature supplied</b>						
Operation and installation instructions	•	•	•	•	•	•

1) HI = Hilight zone; I = Induction.

2) For full installation aperture dimensions see installation instructions.

3) Hob height: is above worktop only.

4) Refer to user instructions before cutting out.

	66331K-MN HK654070XB	66201KF-N HK634030FB	64100KF-N	6010K-MN 6010K-BN
	Ceramic hob	Ceramic hob	Ceramic hob	Ceramic hobs
<b>Hob features</b>				
Number of cooking zones	4	4	4	4
Control position	Front	Front	Front	Side
Control type	Direktouch touch controls	Touch controls	Touch controls	Rotary
Residual heat/hob on indicators	•	•	•	•
Electronic timer	•	•		
Child lock	•	•	•	
Function lock	•	•		
Auto cut-off	•	•	•	
Number of booster zones				
Stop+Go	•	•		
Automatic heat up (AUTOMAX)	•	•		
Pot sensors				
<b>Zone specification</b>				
Front left spec 1)	Triple HI	Triple HI	Dual HI	Dual HI
Front left rating kW	0.8/1.6/2.3	0.8/1.6/2.3	0.75/2.2	0.75/2.2
Front left diameter mm	120/175/210	120/175/210	120/210	120/210
Rear left spec 1)	HI	HI	HI	HI
Rear left rating kW	1.2	1.2	1.2	1.2
Rear left diameter mm	145	145	145	145
Front middle spec 1)				
Front middle rating kW				
Front middle diameter mm				
Rear middle spec 1)				
Rear middle rating kW				
Rear middle diameter mm				
Front right spec 1)	HI	HI	HI	HI
Front right rating kW	1.2	1.2	1.2	1.2
Front right diameter mm	145	145	145	145
Rear right spec 1)	Multi HI	Dual HI	HI	HI
Rear right rating kW	1.5/2.4	0.7/ 1.7	1.8	1.8
Rear right diameter mm	170 x 265	120/180	180	180
<b>Electrical connection</b>				
Total rating (max.) kW	7.1	6.4	6.4	6.4
Fuse rating A	30	30	30	30
<b>Product dimensions 2)</b>				
Height (above worktop) 3) mm	5	5	5	3
Width mm	576	590	590	570
Depth mm	506	520	520	500
Net weight kg	7.7	7.7	7.3	7.7
<b>Aperture dimensions 4)</b>				
Height mm	43	43	43	43
Width mm	560	560	560	560
Depth mm	490	490	490	490
<b>Packaging dimensions</b>				
Height mm	110	115	110	110
Width mm	665	680	665	665
Depth mm	570	575	570	570
Gross weight kg	8.8	8.4	8.1	8.4
<b>Safety and interference suppression</b>				
Low voltage directive LVD	•	•	•	•
Electromagnetic compatibility EMC	•	•	•	•
<b>Literature supplied</b>				
Operation and installation instructions	•	•	•	•

1) HI = Hiilght zone; I = Induction.

2) For full installation aperture dimensions see installation instructions.

3) Hob height: is above worktop only.

4) Refer to user instructions before cutting out.

		75580G-M	79580G-B	75857G-B	65807G-B	99852G-M
<b>Hob features</b>						
Number of cooking zones		5	5	5	4	5
Ignition type		Integral	Integral	Integral	Integral	Integral
Control position		Front	Front	Front	Front	Front
Wok support		•	•	•	•	•
Cast iron pan supports		•	•	•	•	•
Safety thermocouples		•	•	•	•	•
Stability fingers per burner		6	6	8	8	4
Stability feet		•	•	•	•	•
<b>Zone specification</b>						
Front left spec 1)		TC	TC	SR	S	S
Front left rating 2)	kWh	3.8	3.8	1.9	1	1
Front left diameter	mm	122	122	70	54	54
Rear left spec 1)				SR	R	SR
Rear left rating 2)	kWh			1.9	2.9	1.9
Rear left diameter	mm			70	100	70
Front middle spec 1)		S	S	TC		TC
Front middle rating 2)	kWh	1	1	3.8		3.8
Front middle diameter	mm	54	54	122		122
Rear middle spec 1)		SR	SR			
Rear middle rating 2)	kWh	1.9	1.9			
Rear middle diameter	mm	70	70			
Front right spec 1)		SR	SR	S	SR	SR
Front right rating 2)	kWh	1.9	1.9	1	1.9	1.9
Front right diameter	mm	70	70	54	70	70
Rear right spec 1)		SR	SR	SR	SR	SR
Rear right rating 2)	kWh	1.9	1.9	1.9	1.9	1.9
Rear right diameter	mm	70	70	70	70	70
Total rating (max.) 2)	kWh	10.5	10.5	10.5	7.7	10.5
<b>Electrical connection</b>						
Fuse rating	A	3	3	3	3	3
<b>Safety and interference suppression</b>						
Low voltage directive	LVD	•	•	•	•	•
Electromagnetic compatibility	EMC	•	•	•	•	•
Gas directive		•	•	•	•	•
<b>Literature supplied</b>						
Operation and installation instructions		•	•	•	•	•
<b>Product dimensions</b>						
Height (above worktop) 3)	mm	9	8	8	8	8
Width	mm	745	740	680	590	880
Depth	mm	515	510	510	520	510
Net weight	kg	18	16	17.1	15.1	18.7
<b>Aperture dimensions 4)</b>						
Height	mm	40	40	45	30	30
Width	mm	560	560	560	560	830
Depth	mm	480	480	480	480	480
<b>Packaging dimensions</b>						
Height	mm	160	160	150	150	160
Width	mm	860	860	820	710	970
Depth	mm	630	630	630	630	620
Gross weight	kg	19	17	17.8	15.7	19.4

1) S = Simmer burner; R = Rapid burner; SR = Semi-rapid; TC = Triple crown.

2) For gas conversion purpose 3.450 BTU = 1kW.

3) Hob height: is above worktop only.

4) Refer to user instructions before cutting out.

		79852G-M	69802G-M	95852G-M	75852G-M	65852G-M
<b>Hob features</b>						
Number of cooking zones		5	4	6	5	4
Ignition type		Integral	Integral	Integral	Integral	Integral
Control position		Front	Side	Front	Front	Front
Wok support		•	•	•	•	•
Cast iron pan supports		•	•	•	•	•
Safety thermocouples		•	•	•	•	•
Stability fingers per burner		4	4	4	4	4
Stability feet		•	•	•	•	•
<b>Zone specification</b>						
Front left spec 1)		SR	R	R	SR	SR
Front left rating 2)	kWh	1.9	2.9	3	2	2
Front left diameter	mm	70	100	100	70	70
Rear left spec 1)		SR	SR	S	SR	SR
Rear left rating 2)	kWh	1.9	1.9	1	2	2
Rear left diameter	mm	70	70	54	70	70
Front middle spec 1)		TC		SR	TC	-
Front middle rating 2)	kWh	3.8		2	4	-
Front middle diameter	mm	122		62	122	-
Rear middle spec 1)				SR		
Rear middle rating 2)	kWh			2		
Rear middle diameter	mm			70		
Front right spec 1)		S	S	TC	S	S
Front right rating 2)	kWh	1	1	4	1	1
Front right diameter	mm	54	54	122	54	54
Rear right spec 1)		SR	SR	S	R	TC
Rear right rating 2)	kWh	1.9	1.9	1	3	4
Rear right diameter	mm	70	70	54	100	122
Total rating (max.) 2)	kWh	10.5	7.7	13	12	9
<b>Electrical connection</b>						
Fuse rating	A	3	3	3	3	3
<b>Safety and interference suppression</b>						
Low voltage directive	LVD	•	•	•	•	•
Electromagnetic compatibility	EMC	•	•	•	•	•
Gas directive		•	•	•	•	•
<b>Literature supplied</b>						
Operation and installation instructions		•	•	•	•	•
<b>Product dimensions</b>						
Height (above worktop) 3)	mm	8	8	15	15	8
Width	mm	680	580	894	744	594
Depth	mm	510	510	510	510	510
Net weight	kg	15.5	11.7	13.9	13.4	9.7
<b>Aperture dimensions 4)</b>						
Height	mm	30	30	30	30	30
Width	mm	560	550	830	560	560
Depth	mm	480	470	480	480	480
<b>Packaging dimensions</b>						
Height	mm	150	150	150	170	170
Width	mm	790	670	970	880	680
Depth	mm	620	620	620	620	620
Gross weight	kg	16.2	12.4	15.5	14.1	10.3

1) S = Simmer burner; R = Rapid burner; SR = Semi-rapid; TC = Triple crown..

2) For gas conversion purpose 3.450 BTU = 1kW.

3) Hob height: is above worktop only.

4) Refer to user instructions before cutting out.

		DD9996-B	Di9893-M	DD9893-M	DD9863-M	Di9814-M	DD9894-M
		Designer hood	Designer hood	Designer hood	Designer hood	Designer hood	Designer hood
<b>Control</b>							
Control type		Touch	Touch	Touch	Touch	Touch	Touch
Saturation indication		•	•	•	•	•	•
<b>Performance</b>							
Number of motors		1	1	1	1	1	1
Fan speed		Continuous	4	4	4	4	4
Electronic speed control		•	•	•	•	•	•
Intensive setting		•	•	•	•	•	•
Extraction maximum	ca.m3/h	670	500	500	500	490	490
Extraction intensive	ca.m3/h	770	620	620	620	570	570
Recirculation maximum	ca.m3/h	375	330	330	330	370	370
Recirculation intensive	ca.m3/h	460	395	395	395	410	410
Noise (max. setting) extraction	dB(A)	61	60	60	60	63	63
Noise (max. setting) recirculation	dB(A)	60	67	67	67	67.1	67.1
Extraction/recirculation operation		•/•	•/•	•/•	•/•	•/•	•/•
Hobi illumination ( H=Halogen)	Watts	2 x 20H	4 x 20H	2 x 20H	2 x 20H	4 x 20H	2 x 20H
Metal grease filter(s)		•	•	•	•	•	•
<b>Installation height from</b>							
Electric hob	mm	368	500	500	500	500	500
Gas hob	mm	368	650	650	650	650	650
<b>Additional equipment required</b>							
For ducting: Ventilation hose and wall box	LVD	•	•	•	•	•	•
Ventilation hose diameter 1)	mm	150	150	150	150	150	150
For recirculation: Charcoal filter		Included	Included	Included	Included	Included	Included
<b>Appliance dimensions 2)</b>							
Height for extraction	mm	1146	1083-1520	970-1500	970-1500	820-1100	725-1170
Height for recirculation (if different)	mm	1626	1083-1405	970-1500	970-1500	820-1100	725-1170
Width	mm	898	900	900	600	998	898
Depth	mm	350	485	390	390	600	480
Net weight	kg	32.6	52	35.8	35.8	38.5	23.1
<b>Packaging dimensions</b>							
Height	mm	518	640	630	630	1065	650
Width	mm	1075	1030	985	985	555	980
Depth	mm	938	995	965	965	775	630
Gross weight	kg	43	67.1	43	43	47	30.5
<b>Other</b>							
Connected load	Watts	370	255	205	205	255	215
Fuse rating	A	13	13	13	13	13	13
<b>Safety and interference suppression</b>							
Low voltage directive	LVD	•	•	•	•	•	•
Electromagnetic compatibility	EMC	•	•	•	•	•	•
<b>Literature supplied</b>							
Operation and installation instructions		•	•	•	•	•	•

1) CDK6FR - 150mm (6") diameter flexible ducting kit, 3 metre length. For use with all AEG-Electrolux hoods.

2) For full installation aperture dimensions see installation instructions.



		DD9874-M	DD9864-M	DD9693-M	DD9663-M	HD8795-M	HD8760-M
		Designer hood	Designer hood	Designer hood	Designer hood	Designer hood	Designer hood
<b>Control</b>							
Control type		Touch	Touch	Touch	Touch	Touch	Touch
Saturation indication		•	•	•	•	•	•
<b>Performance</b>							
Number of motors		1	1	1	1	1	1
Fan speed		4	4	4	4	4	4
Electronic speed control		•	•	•	•	•	•
Intensive setting		•	•	•	•	•	•
Extraction maximum	ca.m3/h	490	490	510	510	450	450
Extraction intensive	ca.m3/h	570	570	770	770	540	540
Recirculation maximum	ca.m3/h	370	370	340	340	360	360
Recirculation intensive	ca.m3/h	410	410	500	500	400	400
Noise (max. setting) extraction	dB(A)	63	63	57	57	60.7	60.7
Noise (max. setting) recirculation	dB(A)	67.1	67.1	56	56	69	69
Extraction/recirculation operation		•/•	•/•	•/•	•/•	•/•	•/•
Hobi illumination ( H=Halogen)	Watts	2x 20H	2 x 20H	3 x 20H	2 x 20H	3 x 20H	3 x 20H
Metal grease filter(s)		•	•	•	•	•	•
<b>Installation height from</b>							
Electric hob	mm	500	500	650	650	300	300
Gas hob	mm	650	650	650	650	400	300
<b>Additional equipment required</b>							
For ducting: Ventilation hose and wall box	LVD	•	•	•	•	•	•
Ventilation hose diameter 1)	mm	150	150	150	150	150	150
For recirculation: Charcoal filter		Included	Included	Included	Included	Included	Included
<b>Appliance dimensions 2)</b>							
Height for extraction	mm	725-1170	725-1170	795 - 1090	795 - 1090	300 - 1100	300 - 1100
Height for recirculation (if different)	mm	725-1170	725-1170	795 - 1090	795 - 1090	300 - 1100	300 - 1100
Width	mm	698	598	898	598	898	598
Depth	mm	480	480	330	330	335	330
Net weight	kg	24.5	24.5	19.6	16.6	27.6	22.4
<b>Packaging dimensions</b>							
Height	mm	600	600	1001	1001	428	430
Width	mm	980	980	771	771	1001	880
Depth	mm	630	630	540	540	880	720
Gross weight	kg	31	31	27.5	25.5	34.4	26.5
<b>Other</b>							
Connected load	Watts	215	215	390	370	235	235
Fuse rating	A	13	13	13	13	13	13
<b>Safety and interference suppression</b>							
Low voltage directive	LVD	•	•	•	•	•	•
Electromagnetic compatibility	EMC	•	•	•	•	•	•
<b>Literature supplied</b>							
Operation and installation instructions		•	•	•	•	•	•

1) CDK6FR - 150mm (6") diameter flexible ducting kit, 3 metre length. For use with all AEG-Electrolux hoods.  
 CDK5F - 120mm (5") diameter flexible ducting kit, 1 metre length. 100mm (4") reduction collar included. For use with all AEG-Electrolux hoods up to 1 metre ducting.  
 CDK5FR - 120mm (5") diameter flexible ducting kit for ducting hoods situated away from an exterior wall, up to 3 metres. 100mm (4") reduction collar included. For use with all AEG-Electrolux hoods.

2) For full installation aperture dimensions see installation instructions.

		HD8990-M	HD8960-M	HD6470-M	HC5690-M	HC3360-M
		Sensor-controlled hoods	Sensor-controlled hoods	Chimney hoods	Chimney hoods	Chimney hoods
<b>Control</b>						
Control type		Touch	Touch	Push button	Push button	Push button
Saturation indication		•	•		•	
<b>Performance</b>						
Number of motors		1	1	1	1	1
Fan speed		4	4	3	4	3
Electronic speed control		•	•	•	•	•
Intensive setting		•	•		•	
Extraction maximum	ca.m3/h	340	340	470	520	410
Extraction intensive	ca.m3/h	490	490		660	
Recirculation maximum	ca.m3/h	270	270	270	400	210
Recirculation intensive	ca.m3/h	380	380		450	
Noise (max. setting) extraction	dB(A)	60.2	60.2	64	62	62
Noise (max. setting) recirculation	dB(A)	65	65	67	72	64
Extraction/recirculation operation		•/•	•/•	•/•	•/•	•/•
Hobi illumination ( H=Halogen)	Watts	2 x 20H	2 x 20H	2 x 20H	2 x 20H	2 x 20H
Metal grease filter(s)		•	•	•	•	•
<b>Installation height from</b>						
Electric hob	mm	500	500	500	500	500
Gas hob	mm	650	650	650	650	650
<b>Additional equipment required</b>						
For ducting: Ventilation hose and wall box	LVD	•	•	•	•	•
Ventilation hose diameter 1)	mm	150	150	150	150	150
For recirculation: Charcoal filter		Included	Included	Included	Included	Included
<b>Appliance dimensions 2)</b>						
Height for extraction	mm	640-1050	640-1050	660 - 1120	820 - 1275	750 - 1130
Height for recirculation (if different)	mm	720-1140	720-1140	755 - 1220	820 - 1370	750 - 1220
Width	mm	898	598	598 - 698 - 798	898	598
Depth	mm	450	450	500	480	470
Net weight	kg	19.4	17	17.5	17.5	15.8
<b>Packaging dimensions</b>						
Height	mm	630	630	540	580	590
Width	mm	980	680	980	1010	760
Depth	mm	650	650	610	590	630
Gross weight	kg	26.5	22.5	23.2	22.3	20.1
<b>Other</b>						
Connected load	Watts	215	215	200	276	195
Fuse rating	A	13	13	13	13	13
<b>Safety and interference suppression</b>						
Low voltage directive	LVD	•	•	•	•	•
Electromagnetic compatibility	EMC	•	•	•	•	•
<b>Literature supplied</b>						
Operation and installation instructions		•	•	•	•	•

1) CDK6FR - 150mm (6") diameter flexible ducting kit, 3 metre length. For use with all AEG-Electrolux hoods.

CDK5F - 120mm (5") diameter flexible ducting kit, 1 metre length. 100mm (4") reduction collar included. For use with all AEG-Electrolux hoods up to 1 metre ducting.

CDK5FR - 120mm (5") diameter flexible ducting kit for ducting hoods situated away from an exterior wall, up to 3 metres. 100mm (4") reduction collar included. For use with all AEG-Electrolux hoods.

2) For full installation aperture dimensions see installation instructions.

		HD8510-M	EFG70023S	EFG50022S	EFi60013S	EFi60012S
		Professional chimney hood	Canopy unbranded hood	Canopy unbranded hood	Integrated unbranded hood	Integrated unbranded hood
<b>Control</b>						
Control type		Push button	Slider	Slider	Slider	Slider
<b>Performance</b>						
Number of motors		1	1	1	1	1
Fan speed		4	3	3	Continuous	3
Electronic speed control		•		•	•	•
Extraction maximum	ca.m3/h	790	530	290	450	295
Extraction intensive	ca.m3/h					
Recirculation maximum	ca.m3/h	420	350	230	290	130
Recirculation intensive	ca.m3/h					
Noise (max. setting) extraction	dB(A)	73.5	68	64	65.6	65.4
Noise (max. setting) recirculation	dB(A)	72.2	67	63	69.6	67
Extraction/recirculation operation		•/•	•/•	•/•	•/•	•/•
Hobi illumination ( H=Halogen)	Watts	2 x 20W	2 x 40W	2 x 40W	2 x 40W	2 x 40W
Metal grease filter(s)		•	•	•	•	•
<b>Installation height from</b>						
Electric hob	mm	650	650	650	500	500
Gas hob	mm	750	650	650	700	700
<b>Additional equipment required</b>						
For ducting: Ventilation hose and wall box	LVD	•	•	•	•	•
Ventilation hose diameter 1)	mm	150	150	120	120	100
For recirculation: Charcoal filter (optional)		Included	EFF70	EFF70	Type 29	Type 29
<b>Appliance dimensions 2)</b>						
Height for extraction	mm	740 - 1230	305	204	400	400
Height for recirculation (if different)	mm	740 - 1230	305	204		400
Width	mm	1000	702	522	598	598
Depth	mm	515	284	284	270	270
Net weight	kg	21	6.6	4.8	10.8	9.1
<b>Packaging dimensions</b>						
Height	mm	680	400	290	330	330
Width	mm	1330	770	605	473	473
Depth	mm	715	350	370	621	621
Gross weight	kg	25	9.3	5.8	12	10.7
<b>Other</b>						
Connected load	Watts	320	245	175	380	220
Fuse rating	A	13	13	13	13	13
<b>Safety and interference suppression</b>						
Low voltage directive	LVD	•	•	•	•	•
Electromagnetic compatibility	EMC	•	•	•	•	•
<b>Literature supplied</b>						
Operation and installation instructions		•	•	•	•	•

1) CDK6FR - 150mm (6") diameter flexible ducting kit, 3 metre length. For use with all AEG-Electrolux hoods.  
 CDK5F - 120mm (5") diameter flexible ducting kit, 1 metre length. 100mm (4") reduction collar included. For use with all AEG-Electrolux hoods up to 1 metre ducting.  
 CDK5FR - 120mm (5") diameter flexible ducting kit for ducting hoods situated away from an exterior wall, up to 3 metres. 100mm (4") reduction collar included. For use with all AEG-Electrolux hoods.

2) For full installation aperture dimensions see installation instructions.

	C41022G-M	C41029G-M	C41022V-M
	Side/Main		Side/Main
<b>Features</b>			
Number of cooking zones	6	6	5
Ventitherm fan operated cooking	/•	•	/•
Conventional cooking	•/•	•	•/•
Rotitherm	/•	•	/•
Fast heat up	/•	•	/•
Base heat finishing	•/•	•	•/•
Top heat browning	•/•	•	•/•
Dual circuit variable grill	•/•	•	•/•
Cast iron pan supports	•	•	
Residual heat/hob on indicators			•
<b>Control</b>			
Control type	Rotary	Rotary	Rotary
Fully programmable electronic clock	•	•	•
<b>Performance</b>			
Oven temperature range	0-250	0-250	0-250
Energy efficiency class in mode	B/B	B	B/B
Cooktime standard load static	45/40	50	45/40
Cooktime standard load fan	40/NA	45	40/NA
Energy consumption static	0.93/0.91	1.32	0.93/0.91
Energy consumption fan	0.85/NA	1.19	0.85/NA
Standby power	1/1	1	1/1
<b>Zone specification</b>			
Front left spec	Triple Crown wok	Triple Crown wok	Hi-light
Front left rating kW	3.3	3.3	1.0/2.4
Front left diameter mm	100	100	150/240
Front right spec	Auxiliary	Auxiliary	Hi-light
Front right rating kW	1.0	1.0	1.8
Front right diameter mm	60	60	190
Rear left spec	Semi-rapid	Semi-rapid	Hi-light
Rear left rating kW	1.75	1.8	1.2
Rear left diameter mm	75	75	155
Rear right spec	Rapid	Rapid	Hi-light
Rear right rating kW	3.0	2.9	0.7/2.1
Rear right diameter mm	100	100	125/220
Middle front spec	Hi-light	Auxiliary	
Middle front rating kW	1.2	1.0	
Middle front diameter mm	120	75	
Middle rear spec	Hi-light	Fish kettle	Hi-light
Middle rear rating kW	1.2	1.8	1.4/2.2
Middle rear diameter mm	120	Oval	180/90
Ignition type	Integral	Integral	
<b>Design</b>			
Diamond glazed enamel interior	•	•	•
Oven door(s) glazing (T = triple D = double)	D	T	D
Interior lights W	1x15/1x15	1x15	1x15/1x15
Interior lights position	Back/back	Back	Back/back
<b>Equipment supplied</b>			
Chrome grid runners	•/•	•	•/•
Chrome auto-stop non-tip shelves	•/•	•	•/•
Grill/meat pan	•/•	•	•/•
<b>Product dimensions</b>			
<b>Internal oven dimensions (Side/Main)</b>			
Volume (usage) litres	36/61	77	36/61
Height mm	325/325	325	325/325
Width mm	260/460	605	260/460
Depth mm	430/410	390	430/410
<b>Appliance dimensions</b>			
Height mm	900	900	900
Width mm	998	898	898
Depth mm	599	599	599
Net weight kg	129	103	129
<b>Packaging dimensions</b>			
Height mm	1050	1050	1050
Width mm	1030	950	1030
Depth mm	650	650	650
Gross weight kg	149	121	149
<b>Electrical connection</b>			
Voltage V	230/240	230/240	230/240
Frequency Hz	50	50	50
Connected load kW	6.3	2.9	13.6
Fuse rating A	30	13	30
<b>Safety and interference suppression</b>			
Oven power (max) kW	1.9/2.5	2.5	1.9/2.5
Grill power (max) kW	1.2/2.8	2.8	1.2/2.8
Low voltage directive	•	•	•
Electromagnetic compatibility EMC	•	•	•
<b>Literature supplied</b>			
Operation and installation instructions	•	•	•

\*All AEG-Electrolux gas and mixed fuel models are fitted with full safety device suitable for apartments and multi occupancy dwellings.

		SW98820-5R SW98820-5L	SZ91842-4i	SU96000-6i	SU96040-6i	AU96050-6i	AU86055-6i
		In-column wine cooler	In-column food centre	Under counter larder fridge	Under counter fridge with 4* freezer	Under counter freezer	Under counter freezer
<b>Control</b>							
Electronic temperature controls with digital display		•	•		•	•	•
Electromechanical temperature controls		•		•	•	•	•
Adjustable thermostat coin/ knob				•	•	•	•
High temperature warning light/audible buzzer					•	•	•
Door open warning light/audible buzzer		•			•	•	•
Fast freeze LED (yellow)					•	•	•
On LED (green)		•	•		•	•	•
Holiday setting							
<b>Performance</b>							
Energy efficiency class 1)			A+	A+	A+	A+	A
Energy consumption 2)	kWh/year	145	284	117	175	188	215
Freezing capacity	kg/24 hours		3		2.5	18	10
Frozen food rating			4 star		4 star	4 star	4 star
Power cut safe hours 3)			20		13	29	13
Climate class 4)		SN/ST	SN/ST	SN/ST	SN/ST	SN/ST	SN/ST
Noise, IEC 704-3	dB(A)	39	36	35	35	38	40
Temperature divider shelf		•	•				
Reversible door opening			•	•	•	•	•
Adjustable feet				•	•	•	
100% CFC free		•	•	•	•	•	•
100% HFC free		•	•	•	•	•	•
<b>Fridge features</b>							
Gross capacity fridge	litres/cubic feet	169/6	166/5.9	140/4.9	105/3.7		
Net capacity fridge	litres/cubic feet	149/5.3	158/5.6	136/4.8	100/3.5		
Gross capacity longfresh chill zone	litres/cubic feet		78/2.7				
Net capacity longfresh chill zone	litres/cubic feet		78/2.7				
Defrost - fridge		Auto	Auto	Auto	Auto		
Dynamic cooling system							
Cooling system		•	•				
Longfresh chill zone (1-3°C)							
Glass shelves (full depth)		6 St.steel/Alu	2	2	1		
Glass shelves (half depth)			2	2	2		
Deep salad drawer on telescopic runners			•				
Full width transparent salad bin with 2 half width hinged glass lids				•	•		
Transparent salad bin with frosted glass lid							
2 half width salad bins with full width glass cover							
Humidity control (for salad crispers or chill zones)			•				
Dairy compartment with lid			•	•	•		
Full width can shelves / and holders			2/2				
1/2 width sliding shelf / with lid			1/1	1/1	1/1		
Bottle shelf with holder			1	1	1		
Air purifier			•				
Egg tray			•	•	•		
Fridge light		•	•	•	•		
<b>Freezer features</b>							
Gross capacity freezer	litres/cubic feet		29/1		17/0.6	108/3.8	90/3.2
Net capacity freezer	litres/cubic feet		29/1		17/0.6	98/3.4	87/3.1
Frost free							•
Defrost - freezer			Manual		Manual	Manual	Automatic
Frostmatic			•			•	•
Freezer compartments (drawers/ flaps)			1		1	4	3
Ice packs (accumulators)						2	2
<b>Design</b>							
Main colour		White	White	White	White	White	White
Matching fridge/freezer				AU96050-6i	AU96050-6i	SU96000-6i	SU96000-6i
<b>Product dimensions</b>							
Height	mm	873	1773	815	815	815-885	815-885
Width	mm	548	540	596	596	596	596
Depth	mm	545	542	550	550	550	550
Net weight	kg	48	60.5	34	37	38	35
<b>Built-in dimensions</b>							
Built-in height	mm	874	1780	820-870	820-870	820-890	820-890
Built-in width	mm	560	560	600	600	600	600
Built-in depth	mm	550	550	550	550	550	550
Door fixing		Stainless steel/ Glass door	Door on door	Door on door	Door on door	Door on door	Door on door
<b>Packaging dimensions</b>							
Height	mm	960	1860	880	880	880	880
Width	mm	650	610	640	640	640	640
Depth	mm	650	620	620	620	620	620
Gross weight	kg	51	65	33	38	39	36
<b>Electrical connection</b>							
Connected load	W	100	100	90	90	120	80
Fuse rating	A	13	13	13	13	13	13

1) Energy efficiency class based on a scale of A (most efficient) to G (least efficient).

2) Based on standard test results for 24-hours in accordance with EN153. Actual consumption will depend on how the appliance is used and where it is located.

3) Time for food temperature to rise from -18°C to 9°C with the power off and the door remaining closed.

4) Climate class – the product is suitable for use in ambient temperatures of SN: 10-32°C, N: 16-32°C, ST: 18-38°C, T: 18-43°C.

		SK98800-6i	SK 98840-6i	AG98850-5i	SK91200-7i
		In-column larder fridge	In-column fridge with 4" freezer	In-column freezer	In-column larder fridge
<b>Control</b>					
Electronic temperature controls with digital display		•	•	•	•
Electromechanical temperature controls					•
Adjustable thermostat coin/ knob					
High temperature warning light/audible buzzer				•	
Door open warning light/audible buzzer				•	
Fast freeze LED (yellow)				•	
On LED (green)		•	•	•	•
Holiday setting		•			•
<b>Performance</b>					
Energy efficiency class 1)		A+	A+	A+	A+
Energy consumption 2)	kWh/year	123	192	197	131
Freezing capacity	kg/24 hours		2	16	-
Frozen food rating			4 star	4 star	-
Power cut safe hours 3)			12	26	-
Climate class 4)		SN/ST	SN/ST	SN/ST	SN/ST
Noise, IEC 704-3 dB(A)		33	34	35	33
Temperature divider shelf					
Reversible door opening		•	•	•	•
Adjustable feet					
100% CFC free		•	•	•	•
100% HFC free		•	•	•	•
<b>Fridge features</b>					
Gross capacity fridge	litres/cubic feet	156/5.5	122/4.3		227/8
Net capacity fridge	litres/cubic feet	155/5.5	100/3.5		224/7.9
Gross capacity longfresh chill zone	litres/cubic feet				
Net capacity longfresh chill zone	litres/cubic feet				
Defrost - fridge		Auto	Auto		Auto
Cooling system					
Precision cooling system					
Longfresh chill zone (1-3°C)					
Glass shelves (full depth)		2	1		4
Glass shelves (half depth)		2	2		2
Deep salad drawer on telescopic runners					
Full width transparent salad bin with 2 half width hinged glass lids					
Transparent salad bin with frosted glass lid					
2 half width salad bins with full width glass cover		•	•		•
Humidity control (for salad crispers or chill zones)		•	•		•
Dairy compartment with lid		•	•		•
Full width can shelves / and holders		2/2	2/2		3/3
1/2 width sliding shelf / with lid					1/1
Bottle shelf with holder		1	1		1
Air purifier					
Egg tray		•	•		•
Fridge light		•	•		•
<b>Freezer features</b>					
Gross capacity freezer	litres/cubic feet		17/1	110/3.9	
Net capacity freezer	litres/cubic feet		17/1	94/3.3	
Frost free					
Defrost - freezer			Manual	Manual	
Frostmatic			•	•	
Freezer compartments (drawers/ flaps)			1	4	
Ice packs (accumulators)				2	
<b>Design</b>					
Main colour		White	White	White	White
Matching fridge/freezer		AG98850-5i	AG98850-5i	SK98800-6i	AN91250-5i
<b>Product dimensions</b>					
Height	mm	873	873	873	1219
Width	mm	540	540	540	540
Depth	mm	549	549	547	550
Net weight	kg	30	35	35	44
<b>Built-in dimensions</b>					
Built-in height	mm	880	880	880	1225
Built-in width	mm	560	560	560	560
Built-in depth	mm	550	550	550	550
Door fixing		Door on door	Door on door	Door on door	Door on door
<b>Packaging dimensions</b>					
Height	mm	925	925	980	1320
Width	mm	586	586	620	610
Depth	mm	620	620	620	610
Gross weight	kg	31	36	38	46
<b>Electrical connection</b>					
Connected load	W	70	100	80	100
Fuse rating	A	13	13	13	13

	AN91250-5i	SK91800-5i	AG91850-4i	SK91840-5i
	In-column freezer	In-column larder fridge	In-column freezer	In-column fridge with 4* freezer
<b>Control</b>				
Electronic temperature controls with digital display	•	•	•	
Electromechanical temperature controls				•
Adjustable thermostat coin/ knob				•
High temperature warning light/audible buzzer	•		•	
Door open warning light/audible buzzer	•		•	
Fast freeze LED (yellow)	•		•	
On LED (green)	•	•	•	
Holiday setting				
<b>Performance</b>				
Energy efficiency class 1)	A+	A+	A+	A+
Energy consumption 2)	232 kWh/year	145	307	288
Freezing capacity	20 kg/24 hours		20	3
Frozen food rating	4 star		4 star	4 star
Power cut safe hours 3)	24		21	20
Climate class 4)	SN/ST	SN/ST	SN/ST	SN/ST
Noise, IEC 704-3 dB(A)	36	34	38	36
Temperature divider shelf				
Reversible door opening	•	•	•	•
Adjustable feet				
100% CFC free	•	•	•	•
100% HFC free	•	•	•	•
<b>Fridge features</b>				
Gross capacity fridge	litres/cubic feet	332/11.7		277/9.8
Net capacity fridge	litres/cubic feet	330/11.6		267/9.4
Gross capacity longfresh chill zone	litres/cubic feet			
Net capacity longfresh chill zone	litres/cubic feet			
Defrost - fridge		Auto		Auto
Dynamic cooling system				
Cooling system				
Longfresh chill zone (1-3°C)				
Glass shelves (full depth)		4		3
Glass shelves (half depth)		2		2
Deep salad drawer on telescopic runners		•		•
Full width transparent salad bin with 2 half width hinged glass lids				
Transparent salad bin with frosted glass lid				
2 half width salad bins with full width glass cover				
Humidity control (for salad crispers or chill zones)				
Dairy compartment with lid		•		•
Full width can shelves / and holders		3/3		4/4
1/2 width sliding shelf / with lid		1/1		
Bottle shelf with holder		1		1
Air purifier				
Egg tray		•		•
Fridge light		•		•
<b>Freezer features</b>				
Gross capacity freezer	litres/cubic feet	135/4.8	220/7.8	35/1.2
Net capacity freezer	litres/cubic feet	123/4.3	208/7.3	35/1.2
Frost Free		•	•	
Defrost - freezer	Automatic		Automatic	Manual
Frostmatic	•		•	
Freezer compartments (drawers/ flaps)	5		5/2	1
Ice packs (accumulators)	2		2	
<b>Design</b>				
Main colour	White	White	White	White
Matching fridge/freezer	SK91200-7i	AG91850-4i	SK91800-5i	
<b>Product dimensions</b>				
Height	mm	1213	1773	1772
Width	mm	540	540	540
Depth	mm	547	542	547
Net weight	kg	43.5	60.5	61.5
<b>Built-in dimensions</b>				
Built-in height	mm	1225	1780	1780
Built-in width	mm	560	560	560
Built-in depth	mm	550	550	550
Door fixing	Door on door	Door on door	Door on door	Slider
<b>Packaging dimensions</b>				
Height	mm	1300	1860	1860
Width	mm	610	610	610
Depth	mm	600	620	620
Gross weight	kg	47.4	65	66
<b>Electrical connection</b>				
Connected load	W	100	130	120
Fuse rating	A	13	13	13

1) Energy efficiency class based on a scale of A (most efficient) to G (least efficient).

2) Based on standard test results for 24-hours in accordance with EN153. Actual consumption will depend on how the appliance is used and where it is located.

3) Time for food temperature to rise from -18°C to 9°C with the power off and the door remaining closed.

4) Climate class – the product is suitable for use in ambient temperatures of SN: 10-32°C, N: 16-32°C, ST: 18-38°C, T: 18-43°C.

		SN91842-4i	SN71840-5i	SC91843-6i	SC91844-5i	SC91842-5i
		50:50 total frost free fridge-freezer	70:30 frost free fridge-freezer	70:30 fridge-freezer	70:30 fridge-freezer	50:50 fridge-freezer
<b>Control</b>						
Electronic temperature controls with digital display		•		•		
Electromechanical temperature controls			•		•	
Adjustable thermostat coin/knob			•		•	•
High temperature warning light/audible buzzer		•		•		
Fast freeze LED (yellow)		•	•	•	•	
On LED (green)		•		•		
Holiday setting				•		
<b>Performance</b>						
Energy efficiency class 1)		A+	A	A+	A+	A+
Energy consumption 2)		297 kWh/year	314	294	294	285
Total gross capacity		255/9 litres/cubic feet	282/10	285/10	285/10	283/10
Total net capacity		240/8.5 litres/cubic feet	265/9.4	275/9.7	275/9.7	262/9.2
Freezing capacity		10 kg/24 hours	4	13	4	10
Frozen food rating		4 star	4 star	4 star	4 star	4 star
Power cut safe hours 3)		25	21	24	24	24
Climate class 4)		SN/ST	SN/ST	SN/ST	SN/ST	SN/ST
Noise, IEC 704-3		38 dB(A)	38	34	36	36
Reversible door opening		•	•	•	•	•
100% CFC free		•	•	•	•	•
100% HFC free		•	•	•	•	•
<b>Fridge features</b>						
Gross capacity fridge		164/5.8 litres/cubic feet	214/7.6	209/7.4	209/7.4	173/6.1
Net capacity fridge		162/5.7 litres/cubic feet	210/7.4	205/7.2	205/7.2	170/6
Defrost - fridge		Auto	Auto	Auto	Auto	Auto
Air circulation fan		•				
Glass shelves (full depth)		2	3	3	3	2
Glass shelves (half depth)		2	2	2	2	2
2 half width salad bins with full width glass cover		•	•	•	•	•
Humidity control (for salad crispers or chill zones)		•	•	•	•	•
Dairy compartment with lid		•	•	•	•	•
Full width can shelves / and holders		1/1	2/-	2/-	2/2	2/-
1/2 width sliding shelf / with lid		1/1	1/-	1/1	1/1	
Bottle shelf with holder		1/1	1/1	1/1	1/1	1/-
Air purifier		•				
Egg tray		•	•	•	•	•
Fridge light		•	•	•	•	•
<b>Freezer features</b>						
Gross capacity freezer		91/3.2 litres/cubic feet	68/2.4	76/2.7	76/2.7	110/3.9
Net capacity freezer		78/2.7 litres/cubic feet	55/1.9	70/2.5	70/2.5	92/3.2
Frost free		•	•			
Defrost - freezer		Automatic	Automatic	Manual	Manual	Manual
Frostmatic		•	•	•	•	
Freezer compartments (drawers)		4	3	3	3	4
Transparent/solid white freezer compartments		Transparent	White	Transparent	Transparent	Transparent
Ice tray		•	•	•	•	•
Ice scraper				•	•	•
Ice packs (accumulators)		2	2	2	2	2
<b>Design</b>						
Main colour		White	White	White	White	White
Fridge freezer split		50:50	70:30	70:30	70:30	50:50
<b>Product dimensions</b>						
Height		mm 1772	1772	1764	1764	1772
Width		mm 540	540	556	556	540
Depth		mm 547	547	542	542	547
Net weight		kg 59.5	57.5	60	62	57.5
<b>Built-in dimensions</b>						
Built-in height		mm 1780	1780	1780	1780	1780
Built-in width		mm 560	560	560	560	560
Built-in depth		mm 550	550	550	550	550
Door fixing		Slider	Slider	Door on door	Door on door	Slider
<b>Packaging dimensions</b>						
Height		mm 1850	1860	1870	1870	1860
Width		mm 600	610	620	620	610
Depth		mm 620	620	620	620	620
Gross weight		kg 64	62	65	67	62
<b>Electrical connection</b>						
Connected load		W 160	160	150	130	160
Fuse rating		A 13	13	13	13	13

1) Energy efficiency class based on a scale of A (most efficient) to G (least efficient).

2) Based on standard test results for 24-hours in accordance with EN153. Actual consumption will depend on how the appliance is used and where it is located.

3) Time for food temperature to rise from -18°C to 9°C with the power off and the door remaining closed.

4) Climate class – the product is suitable for use in ambient temperatures of SN: 10-32°C, N: 16-32°C, ST: 18-38°C, T: 18-43°C.



		S85628SK1	S75598KG	S75578KG3
		American style food centre	Fridge freezer food centre with wine cooler	European style food centre
<b>Control</b>				
Type of control		Wave Touch temperature control	LED temperature control	LED temperature control
Controls position		External	Top panel	Top panel
No of compressors		1	Twin compressor	Twin compressor
Water dispenser		•		
Ice dispenser		•		
Wine cellar			•	
Visible and audible high temp warning		•	•	•
<b>Performance</b>				
Energy efficiency class 1)		A+	A	A+
Energy consumption kWh/year		444	491	422
Energy consumption per day kWh/day		1.216	1.345	1.156
Climate class 4)		T	SN-N-ST-T	SN-N-ST-T
Noise level db(A)		40	38	40
Precision cooling system		•	•	•
<b>Fridge features</b>				
Gross capacity litres/cubic feet		402/14.2	332/11.72	335/11.82
Net capacity litres/cubic feet		382/13.5	330/11.65	335/11.82
Coolmatic		•	•	•
Shopping mode		•	•	•
Holiday mode		•	•	•
Automatic fridge defrosting		•	•	•
Adjustable glass shelves in fridge		3	6	6
Special compartment		Chill compartment		
Meat keeper				•
Salad drawer		Large salad drawer	Large salad drawer on glide out runners - holds 55 litres	Large salad drawer
Covered dairy compartment		•	•	•
No of door shelves		3	3	4
Bottle shelf		•	•	•
Fridge light		Bulb	Bulb	Bulb
Wine rack (holds 5 bottles)		•	5 inclined wooden shelves in wine cellar - holds 39 bottles	•
Egg tray			•	•
Butter dish		•		•
Quick chill bottle rack				•
Air purifier		•		•
<b>Freezer features</b>				
Gross capacity litres/cubic feet		218/7.69	91/3.21	232/8.19
Net capacity litres/cubic feet		169/2.75	78/2.75	215/7.59
Frostmatic		•	•	•
Star rating 2)		4 Star	4 Star	4 Star
Freezing capacity kg/24 hours		7.5	10	25
Frost-free		•	•	•
Door open indicator		•	•	•
Power cut safe hours 3)		4.7	25	20
Freezer drawers		3	4	5
Fold-down compartment				2
Glass shelf		2		
Ice cube tray		•	•	•
Wine cellar net capacity litres/cubic feet			162/5.72	
Wine cellar gross capacity litres/cubic feet			164/5.79	
Grand total gross capacity litres/cubic feet		620/21.9	587/20.72	567/20.02
Grand total net capacity litres/cubic feet		551/19.45	570/20.12	550/19.42
<b>Design</b>				
Colour		Stainless steel	Stainless steel	Stainless steel
Door opening		Left and Right	Left and Right	Left and Right
<b>Product dimensions</b>				
Height mm		1780	1855	1800
Width mm		910	1090	1190
Depth with closed door mm		710	575	600
Depth with door open mm		1143	1092	1170

1) Energy efficiency class based on a scale of A (most efficient) to G (least efficient).

2) Based on standard test results for 24-hours in accordance with EN153. Actual consumption will depend on how the appliance is used and where it is located.

3) Time for food temperature to rise from -18°C to 9°C with the power off and the door remaining closed.

4) Climate class – the product is suitable for use in ambient temperatures of SN: 10-32°C, N: 16-32°C, ST: 18-38°C, T: 18-43°C.

	F89020iM	F89020Vi	F88020Vi	F75011ViL
<b>Performance</b>				
Capacity (number of IEC place settings)	12	12	12	12
Number of programmes	9	9	8	5
Number of temperatures	6	6	5	4
Auto half load	•	•	•	•
Automatic 45°C - 70°C programme	•	•	•	•
Night cycle	•	•	•	
Quick 55	•	•	•	
Advanced intensive 70°C programme	•	•	•	•
Intensive 70°C programme				
Normal 65°C with prerinse programme	•	•		
Normal 50°C programme				
Energy saving 55°C programme				
Bio 50°C with prerinse programme	•	•	•	•
Glass programme	•	•	•	
Eat-Load-Go programme	•	•	•	•
Plate warmer				
Rinse hold programme	•	•	•	•
Delay start option	•	•	•	•
Multi-tab option				
Drying system	Turbo	Turbo	Active	Active
<b>Features</b>				
LCD display with digital push button controls	•	•		
Programme selection buttons			•	•
LED display with remaining time			•	•
LED programme progress indicators				
Height adjustable upper basket	•	•	•	•
Foldable cup shelves	•	•	•	•
Long stem wine glass holder	•	•	•	•
Adjustable glass support	•	•	•	•
Tall lower basket, front basket handles	•	•	•	•
Foldable bottom plate supports				
Cutlery basket	Fold out	Fold out	Fold out	Fold out
Double fulcrum hinge	•	•	•	•
Interior light	•	•	•	•
3rd spray arm	•	•	•	•
<b>Reassurance</b>				
Aqua control	•	•	•	•
Anti flood device (other)	Floating switch	Floating switch	Floating switch	Floating switch
Worktop steam protection	Metal	Metal	Metal	Metal
Drawer-line adjustment	•			
Top and side fixing brackets	•	•	•	•
Red beam - spot light		•	•	•
End of programme audible buzzer	•	•	•	•
Water softener	•	•	•	•
Salt refill indicator	•	•	•	•
Rinse aid refill indicator	•	•	•	•
<b>Energy efficiency information</b>				
Energy efficiency class 3)	A	A	A	A
Energy consumption 1) kWh	1.05	1.05	1.05	1.05
Wash performance 3)	A	A	A	A
Water consumption litres/cycle	12	12	12	12
Drying performance 3)	A	A	A	A
Noise dB(A) to IEC 704-3	41	41	41	43
Programme time mins 4)	160	160	160	160
Average annual energy consumption 2) kWh/year	231	231	231	231
Average annual water consumption 2) litres/year	2640	2640	2640	2640
Declared programme	Bio 50°C with prerinse	Bio 50°C with prerinse	Bio 50°C with prerinse	Bio 50°C with prerinse
<b>Product dimensions</b>				
Height mm	818	818	818	858
Width mm	596	596	596	596
Depth mm	575	550	550	550
Net weight kg	44.5	45	41.5	43.5
<b>Built-in dimensions</b>				
Built-in height mm	820-880	820-880	820-880	870-940
Built-in width mm	600	600	600	600
Built-in depth mm	600	600	600	600
<b>Packaging dimensions</b>				
Height mm	902	902	902	942
Width mm	650	650	650	650
Depth mm	680	680	680	680
Gross weight kg	47	46.5	43	45.2
<b>Furniture door dimensions</b>				
Optional stainless steel door				
Height mm	528-598	645-715	645-715	684-764
Width mm	596	596	596	596
Weight net/gross kg	2.0 / 10	2.0 / 10	2.0 / 10	2.0 / 7.5
<b>Other</b>				
Voltage/frequency Volt/Hz	220- 240	220- 240	220- 240	220- 240
Connected load kW	2.2	2.2	2.2	2.2
Fuse rating A	13	13	13	13
Water pressure min/max bar	0.5-8 bar	0.5-8 bar	0.5-8 bar	0.5-8 bar
Water pressure min/max Mpa	0.05-0.8 Mpa	0.05-0.8 Mpa	0.05-0.8 Mpa	0.05-0.8 Mpa
Cold water fill	Cold	Cold	Cold	Cold
Electrical/equipment safety regulations	•	•	•	•
Radio/television interference suppression	•	•	•	•
Operation and installation instructions supplied	•	•	•	•

1) Energy consumption is stated in kWh per standard test cycle, using cold water fill. Actual consumption will depend on how the appliance is used.

2) Estimated annual consumption based on 220 washing cycles.

3) Models with an 'A' rated classification offer a higher performance than those with a 'G' rating.

4) Time taken for a standard test cycle, using cold water fill.

	F65011Vi	F85480Vi	F45260Vi
<b>Performance</b>			
Capacity (number of IEC place settings)	12	9	6
Number of programmes	5	5	5
Number of temperatures	4	4	3
Auto half load	•	•	
Automatic 45°C - 70°C programme	•	•	•
Night cycle			•
Quick 55			
Advanced intensive 70°C programme	•	•	
Intensive 70°C programme			•
Normal 65°C with prerinse programme			
Normal 50°C programme			
Energy Saving 55°C programme			•
Bio 50°C with prerinse programme	•	•	
Glass programme			
Eat-Load-Go programme	•	•	
Plate warmer			
Rinse hold programme	•	•	
Delay start option	•	•	•
Multi-tab option			
Drying system	Active	Active	Residual
<b>Features</b>			
LCD display with digital push button controls			
Programme selection buttons	•	•	•
LED display with remaining time	•	•	•
LED programme progress indicators			
Height adjustable upper basket	•	•	
Foldable cup shelves	•	•	
Long stem wine glass holder	•		
Adjustable glass support	•		
Tall lower basket, front basket handles	•		
Foldable bottom plate supports	•	•	
Cutlery basket	Fold out	Fold out	•
Double fulcrum hinge	•		
Interior light			
3rd spray arm	•		
<b>Reassurance</b>			
Aqua control	•	•	
Anti flood device (other)	Floating switch	Floating switch	Floating switch
Worktop steam protection	Metal	Metal	Plastic
Drawer-line adjustment			
Top and side fixing brackets	•	•	
Red beam - spot light	•	•	
End of programme audible buzzer	•	•	
Water softener	•	•	•
Salt refill indicator	•	•	•
Rinse aid refill indicator	•	•	•
<b>Energy efficiency information</b>			
Energy efficiency class 3)	A	A	A
Energy consumption 1) kWh	1.05	0.8	0.63
Wash performance 3)	A	A	A
Water consumption litres/cycle	12	12	7
Drying performance 3)	A	A	B
Noise dB(A) to IEC 704-3	45	47	45
Programme time mins 4)	160	170	150
Average annual energy consumption 2) kWh/year	231	176	138.6
Average annual water consumption 2) litres/year	2640	2640	1540
Declared programme	Bio 50°C with prerinse	Bio 50°C with prerinse	Eco 55°C with prerinse
<b>Product dimensions</b>			
Height mm	818	818	447
Width mm	596	446	545
Depth mm	550	550	494
Net weight kg	38.5	34.5	21.7
<b>Built-in dimensions</b>			
Built-in height mm	820-880	820-880	450
Built-in width mm	600	450	560
Built-in depth mm	600	600	500
<b>Packaging dimensions</b>			
Height mm	902	902	505
Width mm	650	500	605
Depth mm	680	680	595
Gross weight kg	40	36.3	23.5
<b>Furniture door dimensions</b>			
Optional stainless steel door			AEGMIDI-M
Height mm	645-715	645-715	460
Width mm	596	446	596
Weight net/gross kg	2.0 / 10	2.0 / 6.0	2.0 / 5.0
<b>Other</b>			
Voltage/frequency Volt/Hz	220- 240	220- 240	240
Connected load kW	2.2	2.2	1.08
Fuse rating A	13	13	13
Water pressure min/max bar	0.5-8 bar	0.5-8 bar	0.8-10 bar
Water pressure min/max Mpa	0.05-0.8 Mpa	0.05-0.8 Mpa	0.08-1.0 Mpa
Cold water fill	Cold	Cold	Cold
Electrical/equipment safety regulations	•	•	•
Radio/television interference suppression	•	•	•
Operation and installation instructions supplied	•	•	•

1) Energy consumption is stated in kWh per standard test cycle, using cold water fill. Actual consumption will depend on how the appliance is used.

2) Estimated annual consumption based on 220 washing cycles.

3) Models with an 'A' rated classification offer a higher performance than those with a 'G' rating.

4) Time taken for a standard test cycle, using cold water fill.

		L63742VI	L62642VI	L12843VIT	L11842VIT
		Washing machine	Washing machine	Washer dryer	Washer dryer
<b>Capacity</b>					
Wash capacity	kg	6	6	6	6
Dry capacity	kg			4	4
Spin speed	rpm	1400	1200	1400	1200
Wash system		Fuzzy logic	Eco wash	Fuzzy logic	Fuzzy logic
<b>Control</b>					
LCD display		•	•	•	•
Electronic controls		•	•	•	•
Rotary controls		1	1	1	1
Push buttons		7	7	7	7
Programme progress LED		•	•	•	•
Display for programme time, delay time and countdown to programme end		•	•	•	•
Delay start		•	•	•	•
<b>Care</b>					
Cottons/linens		•	•	•	•
Cotton economy				•	•
Cotton prewash				•	•
Economy		•	•	•	•
Synthetics		•	•	•	•
Synthetics + easy iron		•	•	•	•
Delicates programme		•	•	•	•
Handwash / wool plus		•	•	•	•
Coldwash		•	•	•	•
Delicate rinse		•	•	•	•
Stain		•	•	•	•
Refresh		•	•	•	•
Quick wash (reduced time option)		•	•	•	•
Prewash option		•	•		
Extra rinse		•	•	•	•
Sensitive		•	•		
<b>Design</b>					
Colour porthole		Silver	Silver	Silver	Silver
Colour push buttons		Silver	Silver	Silver	Silver
Colour panel		White	White	White	White
Colour knob		White	White	White	White
Large porthole		•	•	•	•
Wide door opening		•	•	•	•
<b>Performance</b>					
<b>Wash/spin only</b>					
Energy efficiency class 1)	wash/spin only	A+	A+	A+	A+
Energy consumption 2)	kWh/cycle	1.02	1.02	1.02	1.02
Average annual energy consumption 4)	kWh/year	204	204	204	204
Water consumption 2)	litres/cycle	42	45	42	42
Average annual water consumption 4)	litres/year	8400	9000	8400	8400
Washing programme time 2)	mins	145	155	145	145
Washing performance (A-G) 2)		A	A	A	A
Spin efficiency (A-G) 2)		B	B	B	B
Water extraction efficiency	%	51	53	49	53
<b>Wash/spin/dry - always using the dryer</b>					
Energy efficiency class 1)	wash/spin/dry			B	C
Energy consumption 3)	kWh/cycle			4.85	5.58
Average annual energy consumption 5)	kWh/year			970	1116
Water consumption 3)	litres/cycle			84	88
Average annual water consumption 4)	litres/year			16800	17600
Washing performance (A-G) 2)				A	A
<b>Product dimensions</b>					
Height	mm	820	820	820	820
Width	mm	600	600	600	600
Depth	mm	541	541	541	541
Net weight	kg	63.9	63.9	67.4	67.4
<b>Built-in dimensions</b>					
Built-in height	mm	825	825	825	825
Built-in width	mm	600	600	600	600
Built-in depth	mm	600	600	600	600
<b>Packaging dimensions</b>					
Height	mm	900	900	900	900
Width	mm	640	640	640	640
Depth	mm	650	650	650	650
Gross weight	kg	63.9	66.5	70	70
<b>Electrical and water connection</b>					
Voltage/frequency	Volt/Hz	240/50	240/50	240/50	240/50
Connected load	kW	2050	2050	2050	2050
Fuse rating	A	13	13	13	13
Water fill		Cold	Cold	Cold	Cold

1) Models with an 'A' rated classification offer a higher performance than those with a 'G' rating.

2) Based on standard test results for 60°C cotton cycle.

3) Based on standard test results for 60°C cotton cycle and "dry cotton" drying cycle.

4) Average annual consumption for a 4 person household based on 200 standard.

5) Average annual consumption for a 4 person household based on 200 standard 60°C cotton cycles, always using the dryer.